

RW 315/2 4+2 W

**Rubber belt, 2 ply, with covers 4+2 mm,
made with type W rubber, the best anti-abrasion class.**

Belt Composition and Technical Data

Type of Fabric	Polyester/Polyamide
Number of Plies	2
Cross-Stability	Suitable for trough
Total Thickness	8,2 mm

Temperature Range	-20°C - +80°C
Tensile Strength	315 N/mm
Min. Pulley Diameters	200 mm
Max. Prod. Width	2.000 mm
Production Process	Rotacure

Top Cover

Rubber Type	SBR/NR Rubber, type W
Thickness Top Cover	4 mm
Colour	Black
Hardness Cover	65° sh A
Profile	Not profiled

Bottom

Rubber Type	SBR/NR Rubber, Type W
Thickness	2 mm
Colour	Black
Hardness Cover	65° shA
Profile	Not profiled

Properties Of The Belt

Anti-Static	Yes
Oil and Grease Resist	No
Sliding Plate Support	No
Idler Support	Yes
Max. Through	45°

- The belts 315/2 4+2, which are not produced by RotaBelting.eu have DIN 22102 type Y anti-abrasion coefficient
- The RotaBelting.eu RW belts are produced with type W rubber, which is 50% more resistant to abrasion compared to most type Y belts

Applications

- Applications demanding a relatively thick cover, used with smaller pulley diameters
- Harvesting and Agro-Food applications



**ROTA
BELTING.eu**

SPECIALISED CONVEYOR PARTS